

TABLE OF DIMENSIONS OF O-RINGS FOR DYNAMIC SEALING AND STATIC SEALING OF CYLINDRICAL SURFACE AND FLAT SURFACE

| NOMINAL SIZE BY JIS B 2401 | DIMENSIONS OF O-RINGS | | NOMINAL SIZE BY JIS B 2401 | DIMENSIONS OF O-RINGS | | |
|----------------------------|-----------------------|-----------------------|----------------------------|-----------------------|-----------------------|---------|
| | THICKNESS (W) | INNER DIAMETER (I.D.) | | THICKNESS (W) | INNER DIAMETER (I.D.) | |
| P3 | 1.9±0.07 | 2.8 | +/-0.14 | P56 | 55.6 | +/-0.50 |
| P4 | | 3.8 | +/-0.14 | P58 | 57.6 | +/-0.52 |
| P5 | | 4.8 | +/-0.15 | P60 | 59.6 | +/-0.53 |
| P6 | | 5.8 | +/-0.15 | P62 | 61.6 | +/-0.55 |
| P7 | | 6.8 | +/-0.16 | P63 | 62.6 | +/-0.56 |
| P8 | | 7.8 | +/-0.16 | P65 | 64.6 | +/-0.57 |
| P9 | | 8.8 | +/-0.17 | P67 | 66.6 | +/-0.59 |
| P10 | | 9.8 | +/-0.17 | P70 | 69.6 | +/-0.61 |
| P10A | | 9.8 | +/-0.17 | P71 | 70.6 | +/-0.62 |
| P11 | | 10.8 | +/-0.18 | P75 | 74.6 | +/-0.65 |
| P11.2 | 11.0 | +/-0.18 | P80 | 79.6 | +/-0.69 | |
| P12 | 11.8 | +/-0.19 | P85 | 84.6 | +/-0.73 | |
| P12.5 | 12.3 | +/-0.19 | P90 | 89.6 | +/-0.77 | |
| P14 | 13.8 | +/-0.19 | P95 | 94.6 | +/-0.81 | |
| P15 | 14.8 | +/-0.20 | P100 | 99.6 | +/-0.84 | |
| P16 | 15.8 | +/-0.20 | P102 | 101.6 | +/-0.85 | |
| P18 | 17.8 | +/-0.21 | P105 | 104.6 | +/-0.87 | |
| P20 | 19.8 | +/-0.22 | P110 | 109.6 | +/-0.91 | |
| P21 | 20.8 | +/-0.23 | P112 | 111.6 | +/-0.92 | |
| P22 | 21.8 | +/-0.24 | P115 | 114.6 | +/-0.94 | |
| P22A | 21.7 | +/-0.24 | P120 | 119.6 | +/-0.98 | |
| P22.4 | 22.1 | +/-0.24 | P125 | 124.6 | +/-1.01 | |
| P24 | 23.7 | +/-0.24 | P130 | 129.6 | +/-1.05 | |
| P25 | 24.7 | +/-0.25 | P132 | 131.6 | +/-1.06 | |
| P25.5 | 25.2 | +/-0.25 | P135 | 134.6 | +/-1.09 | |
| P26 | 25.7 | +/-0.26 | P140 | 139.6 | +/-1.12 | |
| P28 | 27.7 | +/-0.8 | P145 | 144.6 | +/-1.16 | |
| P29 | 28.7 | +/-0.29 | P150 | 149.6 | +/-1.19 | |
| P29.5 | 29.2 | +/-0.29 | P150A | 149.5 | +/-1.19 | |
| P30 | 29.7 | +/-0.29 | P155 | 154.5 | +/-1.23 | |
| P31 | 30.7 | +/-0.30 | P160 | 159.5 | +/-1.26 | |
| P31.5 | 31.2 | +/-0.31 | P165 | 164.5 | +/-1.30 | |
| P32 | 31.7 | +/-0.31 | P170 | 169.5 | +/-1.33 | |
| P34 | 33.7 | +/-0.33 | P175 | 174.5 | +/-1.37 | |
| P35 | 34.7 | +/-0.34 | P180 | 179.5 | +/-1.40 | |
| P35.5 | 35.2 | +/-0.34 | P185 | 184.5 | +/-1.44 | |
| P36 | 35.7 | +/-0.34 | P190 | 189.5 | +/-1.48 | |
| P38 | 37.7 | +/-0.37 | P195 | 194.5 | +/-1.51 | |
| P39 | 38.7 | +/-0.37 | P200 | 199.5 | +/-1.55 | |
| P40 | 39.7 | +/-0.37 | P205 | 204.5 | +/-1.58 | |
| P41 | 40.7 | +/-0.38 | P209 | 208.5 | +/-1.61 | |
| P42 | 41.7 | +/-0.39 | P210 | 209.5 | +/-1.62 | |
| P44 | 43.7 | +/-0.41 | P215 | 214.5 | +/-1.65 | |
| P45 | 44.7 | +/-0.41 | P220 | 219.5 | +/-1.68 | |
| P46 | 45.7 | +/-0.42 | P225 | 224.5 | +/-1.71 | |
| P48 | 47.7 | +/-0.44 | P230 | 229.5 | +/-1.75 | |
| P49 | 48.7 | +/-0.45 | P235 | 234.5 | +/-1.78 | |
| P50 | 49.7 | +/-0.45 | P240 | 239.5 | +/-1.81 | |
| P48A | 47.6 | +/-0.44 | P245 | 244.5 | +/-1.84 | |
| P50A | 49.6 | +/-0.45 | P250 | 249.5 | +/-1.88 | |
| P52 | 51.6 | +/-0.47 | P255 | 254.5 | +/-1.91 | |
| P53 | 52.6 | +/-0.48 | P260 | 259.5 | +/-1.94 | |
| P55 | 54.6 | +/-0.49 | P265 | 264.5 | +/-1.97 | |

TABLE OF DIMENSIONS OF O-RINGS FOR DYNAMIC SEALING AND SEALING OF CYLINDRICAL SURFACE AND FLAT SURFACE

| NOMINAL SIZE BY JIS B 2401 | DIMENSIONS OF O-RINGS | |
|----------------------------|-----------------------|-----------------------|
| | THICKNESS (W) | INNER DIAMETER (I.D.) |
| P270 | 8.4±0.15 | 269.5 |
| P275 | | 274.5 |
| P280 | | 279.5 |
| P285 | | 284.5 |
| P290 | | 289.5 |
| P295 | | 294.5 |
| P300 | | 299.5 |
| P315 | | 314.5 |
| P320 | | 319.5 |
| P335 | | 334.5 |
| P340 | | 339.5 |
| P355 | | 354.5 |
| P360 | | 359.5 |
| P375 | | 374.5 |
| P385 | | 384.5 |
| P400 | | 399.5 |

TABLE OF DIMENSIONS OF O-RINGS FOR STATIC SEALING OF CYLINDRICAL SURFACE AND FLAT SURFACE

| NOMINAL SIZE BY JIS B 2401 | DIMENSIONS OF O-RINGS | |
|----------------------------|-----------------------|-----------------------|
| | THICKNESS (W) | INNER DIAMETER (I.D.) |
| G25 | 3.1±0.1 | 24.4 |
| G30 | | 29.4 |
| G35 | | 34.4 |
| G40 | | 39.4 |
| G45 | | 44.4 |
| G50 | | 49.4 |
| G55 | | 54.4 |
| G60 | | 59.4 |
| G65 | | 64.4 |
| G70 | | 69.4 |
| G75 | | 74.4 |
| G80 | | 79.4 |
| G85 | | 84.4 |
| G90 | | 89.4 |
| G95 | | 94.4 |
| G100 | | 99.4 |
| G105 | 104.4 | |
| G110 | 109.4 | |
| G115 | 114.4 | |
| G120 | 119.4 | |
| G125 | 124.4 | |
| G130 | 129.4 | |
| G135 | 134.4 | |
| G140 | 139.4 | |
| G145 | 144.4 | |
| G150 | 5.7±0.15 | 149.3 |
| G155 | | 154.3 |
| G160 | | 159.3 |
| G165 | | 164.3 |
| G170 | | 169.3 |
| G175 | | 174.3 |
| G180 | | 179.3 |
| G185 | | 184.3 |
| G190 | | 189.3 |
| G195 | | 194.3 |
| G200 | | 199.3 |
| G210 | | 209.3 |
| G220 | | 219.3 |
| G230 | | 229.3 |
| G240 | | 239.3 |
| G250 | | 249.3 |
| G260 | 259.3 | |
| G270 | 269.3 | |
| G280 | 279.3 | |
| G290 | 289.3 | |
| G300 | 299.3 | |